

Pump – Maintenance

Cleaning Products and Equipment

PLAE USA recommends the use of neutral pH (7-9) detergent, Taski Profi, and floor stripper, Taski LinoStrip or JohnsonDiversey Rubber Safe Stripper, to clean and maintain Pump product. Please refer to specific cleaner’s instructions for appropriate application rates and mixture concentrations.

| | Recommended Cleaner | Acceptable Equipment |
|-------------------------|---------------------|---|
| Initial Maintenance | Taski Profi | Auto scrubber with a green or blue pad |
| Regular Maintenance | Taski Profi | Wet or microfiber mop or auto scrubber with a red pad |
| Restorative Maintenance | Taski LinoStrip | Auto scrubber with a green or blue pad |

Important Notes

- Test diluted concentration mixtures on small area of flooring before proceeding with maintenance procedures
- Conduct initial maintenance at least 72 hours after installation
- Read entire maintenance document before beginning maintenance
- Do not use brown or black scrubbing pads
- Do not use steel wool or abrasive brushes, acetone, gasoline, or turpentine

Initial Maintenance

1. Remove all surface soil and debris by sweeping, mopping, or vacuuming
2. Prepare the appropriate concentration mixture of neutral pH (7-9) detergent
3. Apply neutral pH detergent solution with a wet or microfiber mop or auto scrubber
4. Allow detergent solution to stand for 5-10 minutes, but not allow solution to dry up completely
5. Scrub floor with *auto scrubber with a green or blue pad*
6. Pick up solution with a wet vacuum
7. Rinse with clean water
8. Pick up rinse water with wet vacuum
9. Repeat steps 7 & 8, as needed, until all debris is removed
10. Allow to dry thoroughly

Regular Maintenance (Minimum Once Weekly)

Procedures are identical to Initial Maintenance except mixture of neutral pH (7-9) detergent will vary depending on how soiled flooring is and *red pad* is used with auto scrubber

STRENGTH

PLAE

Restorative Maintenance (Once Every 2-3 Years)

1. Remove all surface soil and debris by sweeping, mopping, or vacuuming
2. Prepare the appropriate concentration mixture of floor stripper
3. Apply floor stripper solution with a wet or microfiber mop or auto scrubber
4. Allow floor stripper solution to stand for 7-10 minutes, but not allow solution to dry up completely
5. Scrub floor with *auto scrubber* with a *green or blue pad*
6. Pick up solution with a wet vacuum
7. Rinse with clean water
8. Pick up rinse water with wet vacuum
9. Repeat steps 7 & 8, as needed, until all debris is removed
10. Allow to dry thoroughly

Precautionary Notes

- Entrance mats with black rubber backings may contain rubber black that may discolor Pump to yellowish-brown
- Plywood or Masonite should be used when moving heavy equipment across surface
- Utility vehicles should not be allowed on surface as they may leak oil
- Food and beverages should not be allowed on surface

STRENGTH